



RAVENOL Diesel Performance Optimizer Premium

Premium fuel additive for all diesel engines.

RAVENOL Diesel Performance Optimizer Premium is a premium fuel additive for all diesel engines for cleaning the diesel system, increasing operational safety and for the economic feasibility of diesel engines.

RAVENOL Diesel Performance Optimizer Premium reduces CO₂ and HC emissions, which is tested and certified by the TÜV (Technical Inspection Agency) Thuringia.

RAVENOL Diesel Performance Optimizer Premium cleans the diesel system and the combustion chamber; this leads to a clean fuel injection system.

RAVENOL Diesel Performance Optimizer Premium enables saving fuel. The formation of "acidic" water is prevented and therefore, there is a higher level of protection against corrosion.

RAVENOL Diesel Performance Optimizer Premium increases the lubrication effect for low sulphur fuel.

RAVENOL Diesel Performance Optimizer Premium prolongs the service life of catalytic converters and lambda probes by means of optimum combustion.

Application Notes

RAVENOL Diesel Performance Optimizer Premium is added to the diesel fuel.

Area of application:

- Diesel engines in passenger cars and lorries
- Can be used preventively at every service
- For all diesel fuels, summer and winter diesel
- Suitable for modern common rail and pump nozzle systems

Application: Pour the contents of the container into the tank. Fuel volume up to 50 l of diesel. Minimum fuel capacity according to volume of fuel reserve.

Quality Classifications

RAVENOL Diesel Performance Optimizer Premium is an easy to mix diesel additive.

The efficacy of the CO₂ and HC emissions is tested and certified by the TÜV (Technical Inspection Agency) Thuringia.

Characteristic

RAVENOL Diesel Performance Optimizer Premium offers:

- Certified efficacy by the TÜV (Technical Inspection Agency) Thuringia for the reduction of CO₂ and HC emissions.
- Cleans diesel system and combustion chamber
- Saves fuel
- No "acidic" water, corrosion protection
- Increases the lubrication effect for low sulphur fuel
- Improves the ignitability and reduces "rattling sounds" caused by fuel

Characteristics	Unit	Data	Audit
Colour		gelb	visual
Density at 20°C	kg/m ³	839	EN ISO 12185
Viscosity at 40°C	mm ² /s	7	DIN EN ISO 3104
Flash Point PM	°C	62	DIN ISO 3679

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

23.09.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41