



## RAVENOL Getriebeöl LS SAE 75W-90

RAVENOL Getriebeöl LS SAE 75W-90 is a semi-synthetic lubricant for mechanical transmissions.

RAVENOL Getriebeöl LS SAE 75W-90 is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

### Application Notes

RAVENOL Getriebeöl LS SAE 75W-90 was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

### Quality Classifications

#### Specifications

API GL-5

#### Practice and tested in aggregates with filling

MIL-L-2105D, ZF TE-ML 05C/D

#### Characteristic

RAVENOL LS SAE 75W-90 offers:

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties
- fuel savings

Characteristics	Unit	Data	Audit
Colour		gelb	visual
Density at 20°C	kg/m <sup>3</sup>	863	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	81,5	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	14,5	DIN 51 562
Viscosity index VI		188	DIN ISO 2909
Flash point (COC)	°C	202	DIN ISO 2592
Pourpoint	°C	-42	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

25.10.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41