

RAVENOL Oldtimer 50-er SAE 20W-50 API SC

RAVENOL Oldtimer 50-er SAE 20W-50 API SC is an alloyed multi-grade engine oil designed for use in classic vehicles built prior to 1967. It is manufactured using carefully selected pure mineral raffinates and additives. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication. It is suitable for use in most petrol and diesel engines / classic vehicles built before 1967. Using this oil in modem engines can lead to defective performance or cause damage.

Application Notes

RAVENOL Oldtimer 50-er SAE 20W-50 API SC is designed for use in the engines of vehicles which were built prior to 1967, where the API specification SC is required. Adhere to oil change intervals specified in the manufacturer's instructions.

Specifications

API SC

Characteristic

RAVENOL Oldtimer 50-er SAE 20W-50 API SC offers:

- Corrosion protection
- Good shear stability
- Good oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety also at boundary lubrication conditions
- · Neutrality towards sealing materials
- Very good cold start characteristics
- Prevents the formation of adhesions, varnish, carbon deposits and sludging (black sludge) on cylinders, pistons, valves, spark plugs and in turbochargers

Characteristics	Unit	Data	Audit	
Colour		gelbbraun	visual	
Density at 20°C	kg/m³	884	EN ISO 12185	
Viscosity at 40°C	mm²/s	174,5	DIN 51 562	
Viscosity at 100°C	mm²/s	18,8	DIN 51 562	
Viscosity index VI		122	DIN ISO 2909	
Flash point (COC)	°C	254	DIN ISO 2592	
Pourpoint	°C	-27	DIN ISO 3016	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

26.10.2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther Tel.: 05203/9719-0

Fax.: 052039719-40 / 41