



RAVENOL Oldtimer Regular SAE 30 API SA

RAVENOL Oldtimer Regular SAE 30 API SA is a non-alloy single grade engine oil for use in classic vehicles without an oil filter. It is manufactured using carefully selected pure mineral raffinate. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication. It is suitable for use in most petrol engines / classic vehicles built before 1930. Using this oil in modern engines can lead to defective performance or cause damage.

Application Notes

RAVENOL Oldtimer Regular SAE 30 API SA is designed for use in the engines of vehicles which were built prior to 1930, where the API specification SA is required.

Adhere to oil change intervals specified in the manufacturer's instructions.

Specifications

API SA

Characteristic

RAVENOL Oldtimer Regular SAE 30 API SA offers:

- Corrosion protection
- Good shear stability
- Good oxidation stability
- Excellent viscosity temperature behaviour
- Good cold start characteristics
- Prevents black sludge formation

Characteristics	Unit	Data	Audit
Colour		gelb	visual
Density at 20°C	kg/m ³	885	EN ISO 12185
Viscosity at 40°C	mm ² /s	103,1	DIN 51 562
Viscosity at 100°C	mm ² /s	11,2	DIN 51 562
Viscosity index VI		92	DIN ISO 2909
Flash point (COC)	°C	266	DIN ISO 2592
Pourpoint	°C	-12	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

26.10.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41