

## **RAVENOL Oldtimer Regular SAE 50 API SA**

RAVENOL Oldtimer Regular SAE 50 API SA is a non-alloy single grade engine oil for use in classic vehicles without an oil filter. It is manufactured using carefully selected pure mineral raffinates. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication. It is suitable for use in most petrol engines / classic vehicles built before 1930. Using this oil in modem engines can lead to defective performance or cause damage.

## Application Notes

RAVENOL Oldtimer Regular SAE 50 API SA is designed for use in the engines of vehicles which were built prior to 1930, where the API specification SA is required.

Adhere to oil change intervals specified in the manufacturer's instructions.

## Specifications

API SA

## <u>Characteristic</u>

RAVENOL Oldtimer Regular SAE 50 API SA offers:

- Corrosion protection
- Good shear stability
- Good oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- Good cold start characteristics
- Prevents black sludge formation

Characteristics	Unit	Data	Audit	
Colour		gelb-braun	visual	
Density at 20°C	kg/m <sup>3</sup>	895	EN ISO 12185	
Viscosity at 40°C	mm²/s	207,8	DIN 51 562	
Viscosity at 100°C	mm²/s	17,9	DIN 51 562	
Viscosity index VI		92	DIN ISO 2909	
Flash point (COC)	°C	274	DIN ISO 2592	
Pourpoint	°C	-12	DIN ISO 3016	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

26.10.2016 Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther Tel.: 05203/9719-0 Fax.: 052039719-40 / 41