

RAVENOL RSS SAE 10W-60

RACING

RAVENOL RSS SAE 10W-60 is an ultra-modern high alloyed fully synthetic multigrade engine oil for gasoline engines based on a new and improved formulation of esters and poly-alpha olefins.

Special oil for use by car race, even under the heaviest loads. Its high viscosity index, its very good shear stability and its new highly effective special additives RAVENOL RSS SAE 10W-60 is suitable for extremely sporty driving style. Secure lubrication, even at very high operating temperatures. Excellent protection against wear, corrosion and foam.

Application Notes

RAVENOL RSS SAE 10W-60 may be used as special oil for car racing series even under most difficult conditions.

Quality Classifications

RAVENOL RSS SAE 10W-60 is tried and tested for aggregates specifying:

Areas of application: Opel Motorsport, ADAC GT masters, FIA F3 EUROPEAN Championship

Racetrack partnership: HOCKENHEIMRING, Nürburgring

Characteristic

RAVENOL RSS SAE 10W-60 offers:

- Ultra-modern fully synthetic engine oil for car race
- Fuel saving regarding partial load operation and full power operation
- Very low evaporation tendency
- Very stable and excellent viscosity behaviour
- Very good cold start characteristics
- Safe lubricating layer at very high operating temperatures
- Very good detergent and dispersant characteristics
- Good protection against corrosion and foam formation

Characteristics	Unit	Data	Audit	
Colour		brown	visual	
Density at 20°C	kg/m³	859	EN ISO 12185	
Viscosity at -25°C	mPa.s	5929	ASTM D5293	
Viscosity at 40°C	mm²/s	154,4	DIN 51 562	
Viscosity at 100°C	mm²/s	23,6	DIN 51 562	
Viscosity index VI		184	DIN ISO 2909	
Flash point (COC)	°C	236	DIN ISO 2592	
Pourpoint	°C	- 51	DIN ISO 3016	
Noack Volatility	%	5,4	ASTM D5800/b	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

21.11.2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163

33819 Werther Tel.: 05203/9719-0 Fax.: 052039719-40 / 41