



## RAVENOL SCOOTER 4-Takt Teilsynth.

RAVENOL SCOOTER 4-Takt Teilsynth. is a semi-synthetic high quality green dyed motor oil for small 4-stroke engines. Special ingredients provide for a clean motor and clean intake and exhaust systems. This provides impeccable lubrication and wear protection.

RAVENOL SCOOTER 4-Takt Teilsynth. enables an energy-saving operation of motors because of its additives and the selection of base oils and viscosity characteristics. The special ingredients in RAVENOL SCOOTER 4-Takt Teilsynth. provide for a clean motor and clean intake and exhaust systems. RAVENOL SCOOTER 4-Takt Teilsynth. is the product for an ideal service life of the engine.

### Application Notes

RAVENOL SCOOTER 4-Takt Teilsynth. is used in small 4-stroke engines.

### Quality Classifications

#### Specifications

API SL, SAE 10w-40

#### Practice and tested in aggregates with filling

Yamaha, Honda, Aprilia, Suzuki, Kawasaki, Peugeot, Arctic Cat, Bombardier, Argo, Dinli, Polaris

#### Characteristic

RAVENOL SCOOTER 4-Takt Teilsynth. offers:

- High wear protection
- Fuel saving due to smooth-running properties
- Excellent detergent and dispersant properties
- Prevention of black sludge formation
- Long service life due to outstanding oxidation stability
- Excellent cold start performance
- Very good viscosity-temperature characteristics
- Low tendency to evaporation

| Characteristics    | Unit               | Data  | Audit        |
|--------------------|--------------------|-------|--------------|
| Colour             |                    | green | DIN 51757    |
| Density at 20°C    | kg/m <sup>3</sup>  | 868   | EN ISO 12185 |
| Viscosity at 40°C  | mm <sup>2</sup> /s | 91,3  | DIN 51 562   |
| Viscosity at 100°C | mm <sup>2</sup> /s | 14,0  | DIN 51 562   |
| Viscosity index VI |                    | 157   | DIN ISO 2909 |
| Flash point (COC)  | °C                 | 200   | DIN ISO 2592 |
| Pourpoint          | °C                 | - 35  | DIN ISO 3016 |
| TBN                | mg KOH/g           | 7,1   | DIN ISO 3771 |
| Sulphated ash      | %wt.               | 1,5   | DIN 51 575   |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

18.11.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41